


Certificate of Conformity

Certificate Number: CN-PV-220281

On the basis of the tests undertaken, the sample<s> of the below product have been found to comply with the requirements of the referenced specification<s>/standard<s> at the time the tests were carried out. It does not imply that Intertek has performed any surveillance or control of the manufacture(s). The manufacturer(s) shall ensure that the manufacturing process assures compliance of the production units with the examined products mentioned in this certificate.

Applicant:	Suzhou Johnray Solar Energy Co., Ltd. Room 209, Building 1, Lejihui Business Plaza, New District, Suzhou, Jiangsu, China
Product:	Hybrid Inverter
Ratings & Principle Characteristics:	See appendix of Certificate of Conformity
Model:	JH-6K-ML, JH-5K-ML, JH-4K-ML, JH-3.6K-ML, JH-3K-ML
Brand Name<s>:	
Product Complies with:	UNE 217001:2020 Tests for systems that avoid the discharge of energy to the distribution network
Certificate Issuing Office Name & Address:	Intertek Testing Services Ltd. Shanghai West Area, 2 nd Floor, No. 707, Zhangyang Road China (Shanghai) Pilot Free Trade Zone, Shanghai, P. R. China Accredited by ACCREDIA in accordance with ISO/IEC 17065:2012
Test Report No.<s>:	2209130380GZU-002

Additional information in Appendix.



Signature

Certification Manager: Grady Ye

Date: 12 December 2022



PRD N° 306B

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-220281

MODEL	JH-3K-ML	JH-3.6K-ML	JH-4K-ML	JH-5K-ML	JH-6K-ML
PV String Input data					
Max. Recommended PV power(kW)	7	7	9	9	9
Max.DC voltage(V)	550				
Nominal voltage(V)	360				
MPPT working voltage range(V)	90~550				
Full load dc voltage range(V)	300~450				
Start Voltage/Minimum working voltage(V)	100/80				
Max. input Current of tracker A/tracker B (A)	15/15				
No. of independent MPP trackers/string per MPPT tracker	2/1				
AC Output Data (Grid)					
Rated AC output power(KW)	3	3.6	4	5	6
Max. AC apparent Power(kVA)	3.3	4	4.4	5.5	6.6
Max. AC input power(KW)	6	7.2	8	10	12
AC output voltage	230V, L+N+PE				
Rated AC output frequency	50 /60				
Rated AC output current (A)	13	15.6	18	22	26
Max. AC input current (A)	28	32	38	48	58
Power factor	±0.8				
AC Output Data (Back-up)					
Max. AC output power(KVA)	3.3	4	4.4	5.5	6.6
Rated AC output power(KW)	3	3.6	4	5	6
Rated AC output voltage	230V, L+N+PE				
Rated AC output frequency	50/60				

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-220281

Battery data					
Battery Type	Lithium /Lead-acid				
Nominal voltage(V)	48				
Battery voltage Range(V)	42~59				
Max.charging/discharging current(A)	80/80	80/80	100/100	100/100	100/100
Capacity of battery	25-2000AH				
General Data					
Operating temperature range	-25 °C~ +60 °C				
Environmental Protection	IP65				
Firmware version	HI 1.0				

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-220281

Type of appliance/ Installation	Single-Phase Smart meter / DIN-Rail
Manufacturer / Distributor / Installer	Zhejiang CHINT Instrument&Meter Co., Ltd.
Brand	CHINT
Model/Type	DDSU666
Rating	220/230Vac, 5(80)A , 50/60Hz, 800imp/KWh Power accuracy: Active Class 1.0, Reactive Class 2 IP51 Firmware Version:V1.00



This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.